

**TECHNICAL DESCRIPTION:**

- Door type:** - **AT0022K (Chiller version)**
- Without overlap:**
- Opening speed = 1.5 m/sec.
  - Closing speed = 0.3 m/sec.
- With 100 % overlap:**
- Opening speed = 1.0 m/sec.
  - Closing speed = 0.3 m/sec.
- Canvas:** - Made in 2 designs. One model consists of 2 nos. 0.5 mm polyester canvasses, Blue RAL 5017 or Grey RAL 7040, which overlap each other 100 % to secure density and to avoid cold-conductors. The other design consists of 2 nos. 0.5 mm polyester canvasses, Blue RAL 5017 or Grey RAL 7040, operating as curtains without overlap.
- Canvas color:** - Blue RAL 5017  
Grey RAL 7040
- Side- and top screening:** 0.5 mm polyester canvas in Blue RAL 5017 or Grey RAL 7040.
- Control of door blade:** - Canvas is fitted on a slide valve which is conducted in the track of the anodized aluminium sliding rails.

- Electrical Automation:** - Supplied with professional door automatic that includes possibilities of positioning as well as speed control through frequency transformer. Control panel 1 x 230 V, max 10A.
- Operating equipment:** - Open/close/stop function standard in steering. 2 nos. push bottom panels.
- Max. door size:** - W x H: 3500 x 3500 mm.
- Cleaning of canvas** - Clean water.

**ADDITIONAL EQUIPMENT:**

- Operation equipment:** - Pull cord switches incl. 8 m nylon line.  
- Radar.  
- Photo cell system.  
- Induction loops.  
- Emergency equipment.  
- Switch for other manual door.
- Vision panel:** - Available with vision panel.

**When special door solutions are required, please contact DAN-doors a-s  
Sales Dept.**

We reserve the right for technical improvements.