

Sliding Doors

- For Chill Rooms



Like all DAN-doors, our sliding door epitomises the perfect match between quality materials, precision engineering, first-rate workmanship and timeless elegant design.

Our doors meet the demands for "Foodstuff Hygiene Directive 93/43/EEC"

Sliding Doors

- For Chill Rooms

DAN-doors manufactures a wide range of sliding doors for the food- and other industries. What characterises DAN-doors' sliding doors is their robust construction, which ensures operational reliability even in the most demanding conditions. DAN-doors' sliding doors are made to measure as 1- or 2-leaf doors in the standard version. In addition, DAN-doors can offer special fire-resistant or fire-proof solutions, adapted to the needs of our clients.

Thickness

60 and 100 mm.

Insulation

CFC-free foam provides maximum insulation and minimum energy loss.

Door leaf

Plastisol-coated galvanized steel or stainless steel. Easy to clean, foodsafe, meets the highest hygiene standards.

Frame

1.5 mm stainless steel or 2 mm anodized aluminium. All frames are insulated.

Sliding rail

Robust construction in saltwater-resistant, anodized aluminium with POM rollers. Brackets, stud bolts, washers and nuts in stainless steel.

Recess block

Recess block fitted in the sliding rail, along with the special design of the bottom guide rail and fittings, secures hermetical sealing towards frame and floor.

Rollers

The rollers are made of POM (nylon). The roller brackets, the stud bolt, the washer and the nuts.

Handles

Sturdy stainless steel handles outside and inside handles make the sliding door easy to operate.

Gaskets

Made of approved foodsafe rubber, approved for use in the food industry. Mounted in anodized, closed aluminium profiles.

Automatic control

Available with tooth belt automatic control unit. The unit is mounted on the frame at delivery and all wiring is completed and ready for connection.

Emergency hatch/door

Hatch available in W 600 x H 1000 mm and door in W 800 x H 1800 mm.

Kick plates

Stainless polished steel in standard height 300 or 800 mm x door width.

Locks

Cylinder lock with emergency opening device in black PEHD and stainless steel. Padlock fitting with or without emergency opening in black PEHD.

Windows

Standard sizes – 150 x 300 mm, 400 x 600 mm or 500 x 600 mm.

DAN-doors 
DOORS TO THE WORLD

DAN-doors a-s
Industrivej 19, Stilling
DK-8660 Skanderborg

Tel. +45 87 93 87 00
dd@dan-doors.dk
www.dan-doors.com



We reserve the right to make technical improvements.
November 2013 – www.dan-doors.com