

Sliding Doors

- For Freezer Rooms



Like all DAN-doors, our sliding door epitomises the perfect match between quality materials, precision engineering, first-rate workmanship and timeless elegant design.

Our doors meet the demands for "Foodstuff Hygiene Directive 93/43/EEC"

Sliding Doors

- For Freezer Rooms

DAN-doors manufactures a wide range of sliding doors for freezer rooms for the food- and other industries. What characterises DAN-doors' sliding doors for freezer rooms is their robust construction, which ensures operational reliability even in the most demanding conditions. DAN-doors' sliding doors for freezer rooms are made to measure as 1- or 2-leaf doors in the standard version. In addition, DAN-doors can offer special fire-resistant or fire-proof solutions, adapted to the needs of our clients.

Thickness

100 and 150 mm.

Insulation

CFC-free foam provides maximum insulation and minimum energy loss.

Door leaf

Plastisol-coated galvanized steel or stainless steel. Easy to clean, foodsafe, meets the highest hygiene standards.

Frame

1.5 mm stainless steel or 2 mm anodized aluminium available with heating cables in the frame and threshold. All frames are insulated.

Sliding rail

Robust construction in saltwater-resistant, anodized aluminium with POM rollers. Brackets, stud bolts, washers and nuts in stainless steel.

Recess block

Recess block fitted in the sliding rail, along with the special design of the bottom guide rail and fittings, secures hermetical sealing towards frame and floor.

Rollers

The rollers are made of POM(nylon). The roller brackets, the stud bolt, the washer and the nuts are made of stainless steel.

Handles

Sturdy stainless steel handles outside and inside handles make the sliding door easy to operate.

Heating

The door blade, frame and threshold are provided with an effective heating system which keeps the door frostfree. Alternatively, the door may be delivered without threshold but with extra heating in the lower part of the door leaf.

Blast Freeze

Available for blast freeze applications.

Automatic control

Available with tooth belt automatic. The unit secures a flexible mounting at delivery and all wiring is completed and ready for connection.

Emergency hatch/door

Hatch available in W 600 x H 1000 mm and door in W 800 x H 1800 mm.

Kick plates

Stainless polished steel in standard height 300 or 800 mm x door width.

Locks

Cylinder locks with emergency opening device in black PEHD and stainless steel. Heating units in locks. Padlock fittings with or without emergency opening in black PEHD.

DAN-doors 
DOORS TO THE WORLD

DAN-doors a-s
Industrivej 19, Stilling
DK-8660 Skanderborg

Tel. +45 87 93 87 00
dd@dan-doors.dk
www.dan-doors.com



We reserve the right to make technical improvements.
November 2013 - www.dan-doors.com