

Datasheet - AS0602K

Automatic 60 mm 2-leaf for Chill



Technical data - Overview

| | |
|-----------------------|-----------------------------------------------|
| Std. Height and width | 3200 mm x 3600 mm |
| Automatic | 1 x 230 V / 50 Hz |
| Frame | 1,5 mm Stainless steel AISI 304 |
| Insulation | PIR |
| Sliding rail | Anodized aluminum or Stainless steel AISI 304 |
| Thickness | 60 mm |

Note! Measures which surpasses std. Max width and height, please contact DAN-doors!

| Components | Material/description |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Door leaf material | <ul style="list-style-type: none"> • 1.0 mm Stainless steel AISI304 • 1.0 mm White PVC (Food safe) <p>If you want other surfaces, please contact DAN-doors</p> |
| Frame | <ul style="list-style-type: none"> • 1,5 mm Stainless steel AISI 304 • Frame is always insulated |
| Wheels | <ul style="list-style-type: none"> • Wheels in POM or Stainless steel (64 mm or 80 mm) • Brackets, stud bolt, washer and nuts in Stainless steel |
| Recess | <ul style="list-style-type: none"> • Sliding rail is supplied with recess blocks to ensure hermetic closing towards frame and floor. |
| Gaskets | <ul style="list-style-type: none"> • Quality gaskets approved for use in the food industry. The gaskets are fitted into anodized aluminum profiles. |
| Handle | <ul style="list-style-type: none"> • Frontside – Solid stainless steel handle fitted, on the edge of the door leaf. • Backside – Flush fitted stainless steel handle in a nylon holder. |
| Bottom guides | <ul style="list-style-type: none"> • The bottom guide rail and the bottom guides are manufactured in salt water resistant anodized aluminum. The bottom guides are supplied with solid nylon bushes. |
| Automatic | <p>Tooth belt automatic system (1 x 230 V / 50 Hz)</p> <ul style="list-style-type: none"> • 2 nos. Push buttons supplied as standard. |

| | Extra equipment |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Locks | <p>Cylinder lock with emergency opening device in black PEHD 1000 nylon and stainless steel.</p> <p>Padlock fitting with or without emergency opening device in black PEHD 1000 nylon and stainless steel. (To be locked from the front- or backside)</p> |
| Extra equipment for automatic system | <ul style="list-style-type: none"> • Pull cords w. switch • Remote controls and receiver • Directional radars or scanners • Floor detector (Induction loop) <p>For other solutions, please contact DAN-doors.</p> |
| Window | <p>Std. sizes (Window):</p> <ul style="list-style-type: none"> • 150 x 300 mm • 400 x 600 mm • 500 x 600 mm <p>For other sizes, please contact DAN-doors.</p> |
| Window frame | <ul style="list-style-type: none"> • Anodized aluminum • Stainless steel |
| Glass | <p>Min. 2-layer thermo glass</p> |
| Sliding rail cover | <p>Normally supplied in the same material as the door leaf.</p> <ul style="list-style-type: none"> • White PVC • Stainless steel |
| Emergency hatch/door | <ul style="list-style-type: none"> • Emergency hatch in 600 x 1000 mm • Door in 800 x 1800 mm <p>Regarding handles and locking for hatches and doors, please contact DAN-doors.</p> <p>For other sizes of the hatches, and build in hinged doors, please contact DAN-doors.</p> |
| Kick plates | <p>Material – Stainless steel AISI 304</p> <ul style="list-style-type: none"> • Width x 300 mm (Standard) • Width x 800 mm (Standard) |