

CERTIFIED according to DS 1052.2

TECHNICAL DESCRIPTION:

- Door Type** - **MH0601B - MH0602B**
- Door Blade:** - 1,0 mm stainless steel - AISI 304.
Available in the following surfaces:
- Polished grain 220
 - rigidised
- or
- 1,0 mm galvanized steel – PVC-coated.
Available in the following surfaces:
- white
- (Other qualities and colours are available).
- Thickness - 60 mm
- Insulation - 45 mm Rockwool
- 15 mm Fireboard (gypsum)
- Frame:** - The frame is bended in 1 mm stainless steel (polished grain 220)
- Hinges:** - Stainless steel – AISI 304 – with bronze bushes.
- Handles:** - Handle and key plate in stainless steel with bronze bearing. Locking box is supplied with stainless steel face plate prepared for cylinder. Available with key plate or key plate with hole (prepared for cylinder lock).
- Door Closer:** - Supplied in solid design adjusted to the individual door.
- 2-Leaf Doors:** - Supplied with galvanized espagnolette on stationary door blade.
- Supplied with door selector for closing of active door blade first and extra door closer for stationary door.
- Min/ Max size:** - 1 leaf : W x H: 800 x 2000 / 1100 x 2200

CERTIFIED according to DS 1052.2

2 leaf : W x H: 1400 x 2000 / 2200 x 2200

ADDITIONAL EQUIPMENT:

- Lock:** - Cylinder lock
- Door Closer:** - Available with stainless steel top and arm.
- External doors:** - The door closer is to be fitted on the rear side of the door blade.
- Canopy:** - Recommended for external doors.
- Kick plates:** - Door width x height 300 mm (standard)
- or
- Door width x height 800 mm (max)
- Threshold :** - Available with threshold in stainless steel.

When special door solutions are required, please contact DAN-doors a-s sales dept.

We reserve the right to make technical improvements